

525



Discover why Zamboni is the overwhelming choice
for ice rink operators throughout the world.



The 525 is simple to drive and very easy to operate.

The ergonomically designed operator's compartment has controls and gauges placed for ease of operation and optimal visibility during the resurfacing process. Operation of the machine is made easier with an electronic governor and familiar automobile-style foot controls.

The hydrostatic transmission offers unmatched power at any speed. The smaller, more efficient engine consumes less fuel and provides a cleaner arena environment.

The 525 has it all... reliability, performance and handling.



ZAMBONI®

Nothing else is even close



The Ultimate Machine



Our engine and hydrostatic transmission enable the 525 to use a smaller, more efficient engine and can provide significant fuel savings.

Zamboni ice resurfacers have a well-deserved reputation for producing the finest sheet of ice using our unique down pressure system.

ZAMBONI®

Zamboni USA

Frank J. Zamboni & Co., Inc.
15714 Colorado Ave., Paramount, CA USA 90723-4211
Phone (562) 633-0751 Fax (562) 633-9365

Zamboni Canada

Zamboni Company Ltd.
38 Morton Ave. East, Box 1388, Brantford, ON Canada N3T 5T6
Phone (519) 758-5000 Fax (519) 758-0500

Zamboni Europe

Eigentalsstrasse 1, Box 123, CH-8309 Nuerensdorf, Switzerland
Phone +41 44 837 01 91 Fax +41 44 837 01 80

www.zamboni.com

This brochure is a PDF internet version posted on our website for reference only. The Zamboni Company assumes no responsibility for its content or use. For product and sales information, please contact the Zamboni Company at www.zamboni.com

Serviceability

Wide-open access epitomizes Zamboni's commitment to providing the highest level of serviceability. Daily checks of fluid levels and other maintenance items are easy to accomplish, even with the snow tank down.

Transmission

Continuously variable hydrostatic pump and motor are axial-piston type. Provides superior on-ice power with maximum drawbar pull even at low speeds. Full hydro-dynamic braking.

Drivetrain

Four wheel drive. Rugged Dana Spicer® axles offer the industry's highest manufacturers approved capacities.
Front 4300 lbs. (1950 kg)
Rear 6400 lbs. (2903 kg)

Hydraulics

Powerful double pump for the vertical and horizontal augers delivers strong conveyor performance. Hydraulic down pressure provides superior shaving results. Direct shaft driven "piggy-back" mount for trouble-free service. High quality 16 and 22 micron filters are easy to access.

Construction

Strong 2" x 5" all-welded steel tubing Zamboni chassis. Chassis/axle combination is the key to the 525 having a 16' turning radius - a full 3' tighter than most other machines. High quality primer used throughout. Rust-free polyethylene ice making water tank with easy access cover is standard.

Zamboni and the configuration of the Zamboni® ice resurfacing machine are registered trademarks of Frank J. Zamboni & Co., Inc. Copyright 2007. Printed in Canada GL 07